ARLO PRODUCT DATA SHEET





Available Sizes 600x300x7mm

${m arrho}$ Recycled Content	Up to 37%
Range	Arlo
Category	Stone
Collection	Select Collection
Short Code	AARL2A
Colour	Flint
Finish	Satin
Wall Suitability	Internal Only
Floor Suitability	-
Wet Barefoot	-
Material	Glazed Ceramic
Classificiation	BIII
Light Reflectance Value	55.00
CSV	V2

Samples Service

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379

Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0) | 782 524 | | | | Fax: +44 (0) | 782 577 379

Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Physical Properties			
Test /	Standard	Requirement	Test Result
	Length/Width EN ISO 10545-2	±0.5%≤ ± 2mm	Pass
	Thickness EN ISO 10545-2	±10%≤±0.5mm	Pass
]+	Straightness of Sides EN ISO 10545-2	±0.3% ≤ ± 1.5mm	Pass
-	Rectangularity EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass
$\boxed{ \downarrow \\ \uparrow \uparrow}$	Surface Flatness EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass
	Water Absorption EN ISO 10545-3	10% to 20%	Pass
	Modulus of Rupture EN ISO 10545-4	Ave I5N/mm²	Pass
<u>*</u>	Frost Resistance Not Applicable	N/A	Not suitable
	Chemical Resistance EN ISO 10545-13	Min Class B	Pass
	Stain Resistance EN ISO 10545-14	Min Class 3	Pass
	Fire Rating		Class A I Non Combustible
kg	Weight/m² Thickness 7mm Thickness 10mm		12.35kg 17.78kg



