CLASSICS PRODUCT DATA SHEET



${\cal O}$ Recycled Content	Up to 20%	
Range	Classics	
Category	Stone, Marble	
Collection	Select Collection	
Short Code	CICS6A	
Colour	Slate	
Finish	Satin	
Wall Suitability	Internal Only	
Floor Suitability	-	
Wet Barefoot	-	
Material	Glazed Ceramic	
Classificiation	BIII	
CSV	V2	

Physical Properties			
Test / S	tandard	Requirement	Test Result
	Length/Width EN ISO 10545-2	±0.5%≤ ± 2mm	±0.25%
	Thickness EN ISO 10545-2	±10%≤±0.5mm	±2.5%
- +	Straightness of Sides EN ISO 10545-2	±0.3% ≤ ± 1.5mm	± 0.15%
	Rectangularity EN ISO 10545-2	±0.5% ≤ ± 2mm	± 0.4%
	Surface Flatness EN ISO 10545-2	±0.5% ≤ ± 2mm	±0.2%
	Water Absorption EN ISO 10545-3	10% to 20%	15% to 17%
	Modulus of Rupture EN ISO 10545-4	Ave I5N/mm²	25N/mm²
7.5	Frost Resistance Not Applicable	N/A	Not suitable
$ A \rangle$	Chemical Resistance EN ISO 10545-13	Min Class B	Class A-B (better)
	Stain Resistance EN ISO 10545-14	Min Class 3	Class 3 (better)
	Fire Rating		Class A I Non Combustible
Ng	Weight/m² Thickness 8mm		16kg

Available Sizes 300x200x8mm

Samples Service

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379 Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0) | 782 524 | | | Fax: +44 (0) | 782 577 379 Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate at the time of testing and represent the standard production value. Please note, hadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in line with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential, 25 - 35 signifies a moderate slip potential and 36 represents a low slip potential. All figures are accurate at the time of this data sheets creation (30/04/2025). Johnson Tiles Limited, Harewood Street, Tunstall, Stoke-on-Trent. ST6 SJZ. Registered in England No. 15600432. © 2025 Johnson Tiles. All rights reserved.



