DARLINGTON PRODUCT DATA SHEET



Darlington Range Marble Category Collection Select Collection Short Code DARL2A Colour Stone Gloss Finish Wall Suitability Internal Only Floor Suitability -Wet Barefoot -Material Glazed Ceramic Classificiation BIII 43.00 Light Reflectance Value V2 CSV

Up to 17%

 \mathcal{O} Recycled Content

Physical Properties Test / Standard Requirement Test Result Length/Width ±0.5%≤ ± 2mm Pass EN ISO 10545-2 Thickness ±10%≤±0.5mm Pass EN ISO 10545-2 Straightness of Sides ±0.3% ≤ ± 1.5mm Pass EN ISO 10545-2 Rectangularity $\pm 0.5\% \leq \pm 2mm$ Pass EN ISO 10545-2 Surface Flatness ±0.5% ≤ ± 2mm Pass $\uparrow \uparrow$ EN ISO 10545-2 \bigcirc Water Absorption 10% to 20% Pass EN ISO 10545-3 Modulus of Rupture Ave 15N/mm² Pass EN ISO 10545-4 Frost Resistance 漱 N/A Not suitable Not Applicable **Chemical Resistance** Æ Min Class B Pass EN ISO 10545-13 Stain Resistance Min Class 3 Pass EN ISO 10545-14 Class A1 Non Fire Rating Combustible Weight/m² kg Thickness 7.5mm 10.26kg Thickness 9.5mm 15.17kg Thickness 10mm 17.78kg

Available Sizes 600x300x10mm

Samples Service

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379 Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0) | 782 524 | | | Fax: +44 (0) | 782 577 379 Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate at the time of testing and represent the standard production value. Please note, Inadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in line with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential, 25 - 35 signifies a moderate slip potential and 36+ represents a low slip potential. All rights reserved. No. 15600452.0 2025 Johnson Tiles. All rights reserved.

