DARWIN PRODUCT DATA SHEET



Darwin Range Category **Concrete**, Structure Collection Select Collection DRWN2D Short Code Colour Putty Finish Matt - Rectangular Structure Internal Only Wall Suitability Floor Suitability -Wet Barefoot -Material Glazed Ceramic Classificiation BIII Light Reflectance Value 50.00 V2 CSV

Up to 17%

 \varnothing Recycled Content

Physical Properties			
Test / Standard		Requirement	Test Result
	Length/Width EN ISO 10545-2	±0.5%≤ ± 2mm	Pass
$\rightarrow \square \diamond$	Thickness EN ISO 10545-2	±10%≤ ± 0.5mm	Pass
+	Straightness of Sides EN ISO 10545-2	±0.3% ≤ ± 1.5mm	Pass
-	Rectangularity EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass
${\xrightarrow[]}$	Surface Flatness EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass
	Water Absorption EN ISO 10545-3	10% to 20%	Pass
	Modulus of Rupture EN ISO 10545-4	Ave 15N/mm²	Pass
*	Frost Resistance Not Applicable	N/A	Not suitable
Æ	Chemical Resistance EN ISO 10545-13	Min Class B	Pass
	Stain Resistance EN ISO 10545-14	Min Class 3	Pass
	Fire Rating		Class A1 Non Combustible
kg	Weight/m² Thickness 7.5mm Thickness 8mm		12.58kg 14.85kg

Samples Service

Available Sizes 450x250x7.5mm

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379 Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0) | 782 524 | | | Fax: +44 (0) | 782 577 379 Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate at the time of testing and represent the standard production value. Please note, Inadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in line with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential. 25 - 35 significas at moderate slip potential and 36r represents a low slip potential. All rightres are accurate at the time of this data sheets creation (09/05/2025). Johnson Tiles Limited, Harewood Street, Tunstall, Stoke-on-Trent. ST6 SJZ, Registered in England No. 15600432. 6 2023 Johnson Tiles. All rights reserved.

