EDEN PRODUCT DATA SHEET





Available Sizes 600x300x9mm 1000x333x10.3mm

| arrho Recycled Content | Up to 40% | |
|-------------------------|-------------------|--|
| | | |
| Range | Eden | |
| Category | Marble | |
| Collection | Select Collection | |
| Short Code | EDN01A | |
| Colour | lvory | |
| Finish | Gloss | |
| Wall Suitability | Internal Only | |
| Floor Suitability | - | |
| Wet Barefoot | - | |
| Material | Glazed Ceramic | |
| Classificiation | BIII | |
| Light Reflectance Value | 73.00 | |
| CSV | V2 | |
| | | |

Samples Service

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379

Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0) | 782 524 | | | | Fax: +44 (0) | 782 577 379

Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

| Physical Properties | | |
|--|-----------------|------------------------------|
| Test / Standard | Requirement | Test Result |
| Length/Width EN ISO 10545-2 | ±0.5%≤ ± 2mm | Pass |
| Thickness EN ISO 10545-2 | ±10%≤±0.5mm | Pass |
| Straightness of Sides EN ISO 10545-2 | ±0.3% ≤ ± 1.5mm | Pass |
| Rectangularity EN ISO 10545-2 | ±0.5% ≤ ± 2mm | Pass |
| Surface Flatness EN ISO 10545-2 | ±0.5% ≤ ± 2mm | Pass |
| Water Absorption EN ISO 10545-3 | 10% to 20% | Pass |
| Modulus of Rupture EN ISO 10545-4 | Ave I5N/mm² | Pass |
| Thermal Shock EN ISO 10545-9 | Pass | Pass |
| Frost Resistance Not Applicable | N/A | Not suitable |
| Chemical Resistance EN ISO 10545-13 | Min Class B | Pass |
| Stain Resistance EN ISO 10545-14 | Min Class 3 | Pass |
| UV Colour Resistance | | Unaffected by light |
| Fire Rating | | Class A I Non Combustible |
| Weight/m² Thickness 9mm Thickness 10.3mm | | 14.73kg 18.77kg |



