GLIDE PRODUCT DATA SHEET



Available Sizes 600x300x9mm

 \varnothing Recycled Content Up to 50% Glide Range Category Marble Select Collection Collection Short Code GLD02A Colour White Carrara Finish Gloss Wall Suitability Internal Only Floor Suitability -Wet Barefoot -Material Glazed Ceramic BIII Classificiation Light Reflectance Value 72.00 ٧I CSV

Physical Properties			
Test / Standard		Requirement	Test Result
	Length/Width EN ISO 10545-2	±0.5%≤ ± 2mm	Pass
$\stackrel{\rightarrow}{[]}$	Thickness EN ISO 10545-2	±10%≤ ± 0.5mm	Pass
+	Straightness of Sides EN ISO 10545-2	±0.3% ≤ ± 1.5mm	Pass
-	Rectangularity EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass
$\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}{\stackrel{\mathbf{h}}}}}}}}}}$	Surface Flatness EN ISO 10545-2	±0.5% ≤ ± 2mm	Pass
	Water Absorption EN ISO 10545-3	10% to 20%	Pass
	Modulus of Rupture EN ISO 10545-4	Ave I 5N/mm²	Pass
*	Frost Resistance Not Applicable	N/A	Not suitable
Å	Chemical Resistance EN ISO 10545-13	Min Class B	Pass
	Stain Resistance EN ISO 10545-14	Min Class 3	Pass
	Fire Rating		Class A1 Non Combustible
kg	Weight/m ² Thickness 8mm		18.5kg

Samples Service

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379 Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0) | 782 524 | | | Fax: +44 (0) | 782 577 379 Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate at the time of testing and represent the standard production value. Please note, Inadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in line with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential. 25 - 35 signifies a moderate slip potential and 36r represents a low slip potential. All rights reserved. No. 15600432. © 2023 Johnson Tiles. All rights reserved.



