## **SIENA** PRODUCT DATA SHEET



Siena Range Marble Category Collection Select Collection Short Code SINA2A Colour Grey Finish Gloss Wall Suitability Internal Only Floor Suitability -Wet Barefoot -Material Glazed Ceramic Classificiation BIII 64.00 Light Reflectance Value ٧3 CSV

Up to 20%

 $\varnothing$  Recycled Content

## **Physical Properties** Test / Standard Requirement Test Result Length/Width ±0.5%≤ ± 2mm ±0.25% EN ISO 10545-2 Thickness ±2.5% ±10%≤±0.5mm EN ISO 10545-2 Straightness of Sides ±0.3% ≤ ± 1.5mm ± 0.15% EN ISO 10545-2 Rectangularity $\pm 0.5\% \leq \pm 2mm$ ± 0.4% EN ISO 10545-2 Surface Flatness ±0.5% ≤ ± 2mm ±0.2% $\uparrow \uparrow$ EN ISO 10545-2 $\bigcirc$ Water Absorption 10% to 20% 15% to 17% EN ISO 10545-3 Modulus of Rupture Ave 15N/mm<sup>2</sup> 25N/mm<sup>2</sup> EN ISO 10545-4 Frost Resistance 漱 N/A Not suitable Not Applicable **Chemical Resistance** Æ Min Class B Class A-B (better) EN ISO 10545-13 Stain Resistance Min Class 3 Class 3 (better) EN ISO 10545-14 Class A1 Non

 
 Fire Rating
 Class AT Non Combustible

 Weight/m<sup>2</sup> Thickness 10mm
 18kg

Available Sizes 600x300x10mm

## Samples Service

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379 Email: samples@johnson-tiles.com

**Technical Helpline** 

Tel: +44 (0) | 782 524 | | | Fax: +44 (0) | 782 577 379 Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate as the limitations of the printing process value of the slip resistance. Inadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in lime with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential. 25 - 35 signifies a moderate slip potential and 36+ represents a low slip potential. All rights reserved. No. 15600452.0 2025 Johnson Tiles. All rights reserved.



