
## TERES MOSAICS PRODUCT DATA SHEET



## **Available Sizes**

300x300x4mm (23x23mm)

Range	Teres Mosaics	
Category	Colour, Mosaic	
Collection	Select Collection	
Short Code	TERV44	
Colour	Chestnut	
Finish	Gloss - Square Mosaic	
Wall Suitability	Internal Only	
Floor Suitability	-	
Wet Barefoot	-	
Material	Glass	
Light Reflectance Value	6.00	
CSV	VI	

Physical Properties		
Test / Standard	Requirement	Test Result
Water Absorption EN ISO 10545-3		None
Thermal Shock EN ISO 10545-9	Pass	Pass
Frost Resistance EN ISO 10545-12	Resistant	Resistant
Chemical Resistance EN ISO 10545-13	Min G.B.	Resistant
Stain Resistance EN ISO 10545-14	Minimum Class 3	Class 5
UV Colour Resistance DIN 51094		UV Resistant
Fire Rating		Class A I Non Combustible

## Samples Service

Tel: +44 (0) 1782 524 043 Fax: +44 (0) 1782 577 379

Email: samples@johnson-tiles.com

## Technical Helpline

Tel: +44 (0) 1782 524 111 Fax: +44 (0) 1782 577 379

Email: techadvice@johnson-tiles.com

www.johnson-tiles.com

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate at the time of testing and represent the standard production value. Please note, Inadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in line with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential, 25 - 35 signifies a moderate slip potential and 36+ represents a low slip potential. All figures are accurate at the time of this data sheets creation (01/05/2025). Johnson Tiles Limited, Harewood Street, Tunstall, Stoke-on-Trent. ST6 5JZ. Registered in England No. 15600432. © 2025 Johnson Tiles. All rights reserved.

