

# ZEYA PRODUCT DATA SHEET



## Available Sizes

1200x595x10mm  
745x745x9.7mm

## Samples Service















Tel: +44 (0)1782 524 043  
Fax: +44 (0)1782 577 379  
Email: [samples@johnson-tiles.com](mailto:samples@johnson-tiles.com)

## Technical Helpline

Tel: +44 (0)1782 524 111  
Fax: +44 (0)1782 577 379  
Email: [techadvice@johnson-tiles.com](mailto:techadvice@johnson-tiles.com)

[www.johnson-tiles.com](http://www.johnson-tiles.com)

Range	<b>Zeya</b>
Category	<b>Stone, Floor Tiles, PTV 36+ Tiles</b>
Collection	<b>Select Collection</b>
Short Code	<b>ZEY03G</b>
Colour	<b>Taupe</b>
Finish	<b>Grip</b>
Wall Suitability	<b>Internal &amp; External</b>
Floor Suitability	<b>Internal &amp; External</b>
Wet Barefoot	<b>Yes</b>
Material	<b>Glazed Porcelain</b>
Classification	<b>Bla</b>
Light Reflectance Value	<b>41.00</b>
CSV	<b>V3</b>
PTV (96)	<b>Wet 36+ Dry 36+</b>
PTV (55)	<b>Wet 36+</b>
R Value	<b>-</b>
Wet Ramp	<b>-</b>
PEI	<b>III</b>
Traffic	<b>Light Commercial</b>

Physical Properties			
Test / Standard		Requirement	Test Result
	<b>Length/Width</b> EN ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass
	<b>Thickness</b> EN ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
	<b>Straightness of Sides</b> EN ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
	<b>Rectangularity</b> EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass
	<b>Surface Flatness</b> EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass
	<b>Water Absorption</b> EN ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\%$
	<b>Modulus of Rupture</b> EN ISO 10545-4	$\geq 35\text{N/mm}^2$	$\geq 35\text{N/mm}^2$
	<b>Thermal Shock</b> EN ISO 10545-9	Pass	Pass
	<b>Frost Resistance</b> EN ISO 10545-12	Resistant	Resistant
	<b>Chemical Resistance</b> EN ISO 10545-13	Min Class B	Min Class B
	<b>Stain Resistance</b> EN ISO 10545-14	Min Class 3	Min Class 3
	<b>UV Colour Resistance</b>		Unaffected by light
	<b>Fire Rating</b> Not Applicable	N/A	Class A I FL Non Combustible
	<b>Weight/m²</b>		
	Thickness: 8.5mm		17.8kg
	Thickness: 8.7mm		18.2kg
	Thickness: 9.5mm		20.25kg
	Thickness: 9.7mm		19.63kg
	Thickness: 10mm		22.3kg
	Thickness: 20mm		38.2kg

Tile colours shown of the tile product on this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. The slip resistance values provided are accurate at the time of testing and represent the standard production value. Please note, inadequate cleaning and maintenance will lead to a significant reduction in the slip resistance of any tiles. The pendulum test results are displayed in line with The Health & Safety Executive guidelines whereby 0 - 24 represents a high slip potential, 25 - 35 signifies a moderate slip potential and 36+ represents a low slip potential. All figures are accurate at the time of this data sheets creation (30/04/2025). Johnson Tiles Limited, Harewood Street, Tunstall, Stoke-on-Trent. ST6 5JZ. Registered in England No. 15600432. © 2025 Johnson Tiles. All rights reserved.

EST. 1901  
**JOHNSON  
TILES**