OSLO

GLAZED PORCELAIN | FLOOR & WALL TILES

WOOD ABSOLUTE

UP TO 30% RECYCLED CONTENT

36+ PTV (4S) RATING

36+ PTV (TRL) RATING

RECTIFIED EDGE PRODUCTS

NATURAL COLOUR PALETTE

JOHNSON · TILES

MADE IN THE UK SINCE 1901

OSLO

Showcasing a bleached, aged look, this wood effect range features 4 colours – Raw, Weathered White, Aged Grey, and Carbon Grey. Natural and Grip finishes are available in this range, with the Grip achieving a PTV 36+ slip resistance rating. Two large format plank options of 1200x200mm and 750x150mm are featured, perfect for opening out spaces and adding a nature-inspired aesthetic to any design.

Front Cover Image: Raw Natural 1200x200mm - OSL01N.

Roomset Photography

Aged Grey Natural 750x150mm - OSL03N

Weathered White Grip 1200x200mm - OSL02G

Raw Natural 1200x200mm - OSL01N

Colours & Product Codes

V3: Moderate to High Shade Variation

RAW

Ⓝ OSL01N + Ⓖ OSL01G

PEI: IV LRV: 53

WEATHERED WHITE

Ⓝ OSL02N + Ⓖ OSL02G

PEI: IV LRV: 72

AGED GREY

Ⓝ OSL03N + Ⓖ OSL03G

PEI: IV LRV: 42

CARBON GREY

Ⓝ OSL04N + Ⓖ OSL04G

PEI: IV LRV: 15

Sizes, Finishes & Availability

1

Ⓡ

2

Ⓡ

#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	1200x200mm	Ⓝ Natural	All Colours Shown	10.5mm	6 Tiles	1.44 m²	35.00 kg
		Ⓖ Grip	All Colours Shown	10.5mm	6 Tiles	1.44 m²	35.00 kg
2	750x150mm	Ⓝ Natural	All Colours Shown	9mm	10 Tiles	1.13 m²	21.50 kg
		Ⓖ Grip	All Colours Shown	9mm	10 Tiles	1.13 m²	21.50 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value. Ⓡ Rectified Edge

Additional Fittings

V3: Moderate to High Shade Variation

RAW

(N) OLS1NS PEI: IV LRV: 53

WEATHERED WHITE

(N) OLS2NS PEI: IV LRV: 72

AGED GREY

(N) OLS3NS PEI: IV LRV: 42

CARBON GREY

(N) OLS4NS PEI: IV LRV: 15



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	1200x95mm Round Top Skirting	(N) Natural	All Colours Shown	10.5mm	10 Tiles	12.00 lm	26.00 kg
2	750x70mm Round Top Skirting	(N) Natural	All Colours Shown	9mm	14 Tiles	10.50 lm	14.00 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.

Weathered White Grip 1200x200mm - OSL02G

Technical Data

Specification

Range	Size / Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Oslo	All Sizes Shown (N)	Internal & External	Internal Only	-	V3	Glazed Porcelain [BIa]
	All Sizes Shown (G)	Internal & External	Internal & External	Yes	V3	Glazed Porcelain [BIa]

Floor Values

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
(N) Natural	All Colours Shown	Dry 36+ Wet 36+	-	R10	A	IV	Commercial
(G) Grip	All Colours Shown	Dry 36+ Wet 36+	Wet 36+	R11	B	IV	Commercial

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute.

Physical Properties

Test / Standard	Requirement	Test Result	Test / Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.6% ≤ ± 2mm	**Pass**	**Modulus of Rupture** EN ISO 10545 - 4	Min. 35N / mm²	**≥ 35N / mm²**
Thickness EN ISO 10545 - 2	± 5% ≤ ± 0.5mm	**Pass**	**Thermal Shock** EN ISO 10545 - 9	Pass	**Pass**
Straightness of Side EN ISO 10545 - 2	± 0.5% ≤ ± 1.5mm	**Pass**	**Frost Resistance** EN ISO 10545 - 12	Resistant	**Resistant**
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	**Pass**	**Chemical Resistance** EN ISO 10545 - 13	Min. Class B	**Min. Class B**
Surface Flatness EN ISO 10545 - 2	± 0.5% ≤ ± 0.5mm	**Pass**	**Stain Resistance** EN ISO 10545 - 14	Min. Class 3	**Min. Class 3**
Water Absorption EN ISO 10545 - 3	≤ 0.5%	**≤ 0.5%**	**Fire Rating**	-	**Class A1 FL Non Combustible**
Weight / M²	**24.31 kg** 10.5mm thick	**19.12 kg** 9mm thick			

Note: All products are classed as BIa - Glazed Porcelain. All products conform to BS EN 14411.

Sustainability Information

Range	Material	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Oslo	Glazed Porcelain [BIa]	-	Up tp 30%	Some Part Recycled	Up to 100%

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.

bsi. ISO 9001 Quality Management FM26818

bsi. ISO 14001 Environmental Management EMS40817

For more information about Oslo or any of our other product ranges simply visit

www.johnson-tiles.com

Where To Find Us

Johnson Tiles
Harewood Street,
Tunstall,
Stoke on Trent,
Staffordshire,
ST6 5JZ

Tel: +44 (0)1782 575 575
Fax: +44 (0)1782 577 377
Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043
Fax: +44 (0)1782 577 379
Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111
Fax: +44 (0)1782 577 379
Email: techadvice@johnson-tiles.com

Launched: July 2021

JOHNSON · TILES
MADE IN THE UK SINCE 1901