REFINE WALL

GLAZED CERAMIC | WALL TILES

STONE STRUCTURE (ABSOLUTE)
















REFINE WALL

This architectural wall collection provides a classic palette of four neutral tones. Understated colours are paired with geometric designs to create a striking combination. This stone-effect range features three profiles: Peak, Calm, and Prints. Peak showcases chevron patterning, with Calm and Prints featuring linear structures. Explore the possibilities with horizontal or vertical lay patterns.

Front Cover Image: Basalt Prints Structure Natural 900x300mm - REF04P with Refine Basalt Natural 900x900mm - REF04N.



www.johnson-tiles.com











Colours & Product Codes V2: Low to Moderate Shade Variation



DUNE LRV: 62 CALM STRUCTURE Product Code: N REFOIC



PEAK STRUCTURE Product Code: N REFOIK



PRINTS STRUCTURE Product Code: N REFOIP



PEWTER LRV: 29 CALM STRUCTURE Product Code: N REF02C



PEWTER LRV: 29 PEAK STRUCTURE Product Code: N REF02K



PEWTER LRV: 29 PRINTS STRUCTURE Product Code: N REF02P




LAVASTONE LRV: 18 CALM STRUCTURE Product Code: N REF03C



LAVASTONE LRV: 18 PEAK STRUCTURE Product Code: N REF03K



LAVASTONE LRV: 18 PRINTS STRUCTURE Product Code: N REF03P



BASALT LRV: 19 CALM STRUCTURE Product Code: N REF04C




BASALT LRV: 19 PEAK STRUCTURE Product Code: N REF04K



BASALT LRV: 19 PRINTS STRUCTURE Product Code: N REF04P

Size Formats Finishes & Availability



#	Sizes	Finish Type	Colour Availability	Thickness	Pz / Box	M2 / Box	Kg / Box
1	900x300mm Calm Structure	N Only	All Colours Shown	Hmm	4 Tiles	1.07 m²	19.49 kg
2	900x300mm Peak Structure	N Only	All Colours Shown	Hmm	4 Tiles	1.07 m²	19.49 kg
3	900x300mm Prints Structure	N Only	All Colours Shown	Hmm	4 Tiles	1.07 m²	19.49 kg

Key to Finishes: Natural

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.

Rectified Edge





Specification

Range	Size / Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Refine Wall	All Sizes Shown N	Internal Only	-	-	V2	Glazed Ceramic [BIII]

Physical Properties - Ceramic [BIII] Ductile

Test / Standard	Requirement	Test Result	Test	/ Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass		Modulus of Rupture EN ISO 10545 - 4	Min. I 5N / mm²	≥ 15N / mm²
Thickness EN ISO 10545 - 2	± 10% ≤ ± 0.5mm	Pass	业	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	Pass	*	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass		Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A
Surface Flatness EN ISO I 0545 - 2	± 0.5% ≤ ± 2mm	Pass	A	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 5
Water Absorption EN ISO 10545 - 3	10% to 20%	10% to 20%		Fire Rating	-	Class A I Non Combustible
kg Weight / M²	18.05 kg I I mm thick					

Note: All Ceramic [BIII] products listed in this overview conform to BS EN 14411.

Range		EPD	Recycled Content of the Tiles		Recyclable Content of the Packaging
Refine Wall	Glazed Ceramic [BIII]	Yes	Up to 30%	Up to 100% (Boxes)	Up to 100% (Boxes)

Note: EPD: Environmental Product Declaration for the products shown in this overview can be found on the Refine Wall pages on our website.

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- \bullet Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- \bullet Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.







 ,

For more information about Refine Wall or any of our other product ranges simply visit www.johnson-tiles.com | f > 0 p in D

Where To Find Us

Johnson Tiles Harewood Street, Tunstall,

Stoke on Trent, Staffordshire,

ST6 5JZ

Tel: +44 (0)1782 575 575 Fax: +44 (0)1782 577 377 Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379

 ${\bf Email: samples@johnson-tiles.com}$

Technical Helpline

Tel: +44 (0) | 782 524 | | | | | Fax: +44 (0) | 782 577 379

Email: techadvice@johnson-tiles.com

