FLARE

GLAZED CERAMIC | WALL TILES

PLAIN COLOUR TILES ABSOLUTE

UP TO 30% RECYCLED CONTENT

epd

JOHNSON · TILES

MADE IN THE UK SINCE 1901

FLARE

A simple range of glazed ceramic wall tiles, Flare offers three tones of Simply White, Eggshell, and Linen to add a sense of warmth and calm to any design scheme. Featured in a Gloss finish in all three colours, with Simply White also offering a Satin, Flare is available in 1200x400mm.

Front Cover Image: Simply White Gloss 1200x400mm - FLA01G

Linen Gloss 1200x400mm - FLA03G

Roomset Photography

Linen Gloss 1200x400mm - FLA03G

Eggshell Gloss 1200x400mm - FLA02G



Simply White Gloss 1200x400mm - FLA01G

Colours & Product Codes

V1: Low Shade Variation

SIMPLY WHITE

G FLA01G + S FLA01S LRV: 90

EGGSHELL

G FLA02G LRV: 77



LINEN

G FLA03G LRV: 55

Sizes, Finishes & Availability

1



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	1200x400mm	G Gloss	All Colours Shown	12.5mm	2 Tiles	0.96 m²	20.30 kg
		S Satin	Simply White Only	12.5mm	2 Tiles	0.96 m²	20.30 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.

Technical Data

Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Flare	All Sizes Shown	Internal Only	-	-	V1	Glazed Ceramic [BIII]

Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm²	Pass
Thickness EN ISO 10545 - 2	± 10% ≤ ± 0.5mm	Pass	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	Pass	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A
Surface Flatness EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Pass
Water Absorption EN ISO 10545 - 3	10% to 20%	Pass	Fire Rating	-	Class A1 Non Combustible
Weight / M²	22.00 kg 12.5mm thick				

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

Sustainability Information

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD	SKA Rating
Flare	Glazed Ceramic [BIII]	Up to 30%	Up to 100% (Boxes)	Up to 100% (Boxes)	Yes	-

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Flare pages on our website.

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.

bsi. ISO 9001 Quality Management FM26818

bsi. ISO 14001 Environmental Management EMS40817

For more information about Flare or any of our other product ranges simply visit **www.johnson-tiles.com**

Where To Find Us

Johnson Tiles
Harewood Street,
Tunstall,
Stoke on Trent,
Staffordshire,
ST6 5JZ

Tel: +44 (0)1782 575 575
Fax: +44 (0)1782 577 377
Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043
Fax: +44 (0)1782 577 379
Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111
Fax: +44 (0)1782 577 379
Email: techadvice@johnson-tiles.com

Launched: May 2016

JOHNSON · TILES
MADE IN THE UK SINCE 1901