
## ZODIAC

GLAZED PORCELAIN | FLOOR & WALL TILES

STONE STRUCTURE (ABSOLUTE)
















### ZODIAC

Zodiac has a classic colour palette with 4 colour options of Nickle, Aluminium, Titanium and Gunmetal. With a stone effect look offering natural variation, Zodiac offers 4 different finishes: Natural with a smooth, even finish; Slate Structure exhibiting a dappled effect; Textured Structure with a riven raised surface; and Rock Structure which displays fractured linear channels for added depth and dimension. Both the Textured and Rock Structures offer a PTV 36+ slip resistance rating, perfect for indoor and outdoor use. Decorative mosaic options are also available for wall applications, showcasing a mix of Natural & Polished finishes, with geometric shapes forming 890x300mm and 600x600mm sizes.

Front Cover Image: Gunmetal Rock Structure Natural II90x600mm & II90x300mm - ZOD04R and Aluminium Slate Structure Natural 890x890mm - ZOD02S.









#### **Colours & Product Codes**

V2: Low to Moderate Shade Variation





NICKLE
TEXTURED STRUCTURE
N ZODOIT PEI: V LRV: 55



ALUMINIUM
TEXTURED STRUCTURE
N ZOD02T PEI: IV LRV: 54



TITANIUM
TEXTURED STRUCTURE
N ZODO3T PEI: IV LRV: 38



GUNMETAL
TEXTURED STRUCTURE
N ZOD04T PEI:III LRV: 16



NICKLE
ROCK STRUCTURE

N ZODOIR PEI: V LRV: 55



ALUMINIUM
ROCK STRUCTURE

N ZOD02R PEI: IV LRV: 54



TITANIUM

ROCK STRUCTURE

N ZOD03R PELIV LRV: 38




GUNMETAL
ROCK STRUCTURE

N ZOD04R PEI:III LRV: 16



NICKLE
MIXED MOSAIC (2 PIECE SET)

X ZODIMM LRV. 55





ALUMINIUM
MIXED MOSAIC (2 PIECE SET)

X ZOD2MM LRV. 54



ALUMINIUM
MIXED MOSAIC (2 PIECE SET)

X ZOD2MM LRV. 54




TITANIUM
MIXED MOSAIC (2 PIECE SET)


X ZOD3MM LRV. 38



TITANIUM
MIXED MOSAIC (2 PIECE SET)

X ZOD3MM LRV. 38






GUNMETAL
MIXED MOSAIC (2 PIECE SET)

X ZOD4MM LRV: 16



#### Sizes, Finishes & Availability



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	1190x600mm *	N Natural	All Colours Shown	10.5mm	I Tile	0.72 m²	17.40 kg
2	1190x300mm *	N Natural	All Colours Shown	10.5mm	2 Tiles	0.72 m²	17.40 kg
3	890x890mm	N Natural	All Colours Shown	10.5mm	I Tile	0.80 m²	19.40 kg
4	890x300mm *	N Natural	All Colours Shown	10.5mm	3 Tiles	0.8 l m²	19.36 kg
5	600x600mm	N Natural	All Colours Shown	10.5mm	3 Tiles	1.08 m²	24.40 kg
6	890x300mm Mixed Mosaic (2 Piece Set – A & B)	🛭 Natural / Polished	All Colours Shown	I 0.5mm	2 Sheets	0.54 m²	12.90 kg
7	600x600mm Mixed Mosaic (2 Piece Set - A & B)	X Natural / Polished	All Colours Shown	10.5mm	2 Sheets	0.72 m²	16.27 kg

<sup>\*</sup> Rock structure is only available in 1190x600mm, 1190x300mm & 890x300mm size formats. All other structures are available in all size fotmats.

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value. (R) Rectified Edge





#### **Additional Fittings**

V2: Low to Moderate Shade Variation





ALUMINIUM

N ZOD2NS PEI: IV LRV: 54

**GUNMETAL** 


#### TITANIUM N ZOD3NS PEI: IV LRV: 38

Round Top Skirting





Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.





#### **Technical Data**

#### **Specification**

Range	Size / Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Zodiac	All Sizes Shown N	Internal & External *	Internal & External **	Yes **	V2	Glazed Porcelain [Bla]

#### Floor Values

Finish / Structure	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
	Gunmetal	Dry 36+ Wet 25 - 35	-	RIO	А	Ш	Light Commercial
N Natural	Aluminium & Titanium	Dry 36+ Wet 25 - 35	-	RIO	А	IV	Commercial
	Nickle	Dry 36+ Wet 25 - 35	-	RIO	А	V	Heavy Commercial
	Gunmetal	Dry 36+ Wet 36+	-	RI0	А	Ш	Light Commercial
Natural / Slate	Aluminium & Titanium	Dry 36+ Wet 36+	-	RIO	А	IV	Commercial
	Nickle	Dry 36+ Wet 36+	-	RIO	А	V	Heavy Commercial
	Gunmetal	Dry 36+ Wet 36+	Wet 36+	RII	С	III	Light Commercial
Natural / Textured	Aluminium & Titanium	Dry 36+ Wet 36+	Wet 36+	RII	С	IV	Commercial
	Nickle	Dry 36+ Wet 36+	Wet 36+	RII	С	V	Heavy Commercial
	Gunmetal	Dry 36+ Wet 36+	_	RIO	В	III	Light Commercial
N Natural / Rock	Aluminium & Titanium	Dry 36+ Wet 36+	-	RIO	В	IV	Commercial
	Nickle	Dry 36+ Wet 36+	-	RI0	В	V	Heavy Commercial

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 95. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute.

#### **Physical Properties**

Test / Standard	Requirement	Test Result	Test / Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.6% ≤ ± 2mm	± 0.4%	Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm²	≥ 45N / mm²
Thickness EN ISO 10545 - 2	± 5% ≤ ± 0.5mm	± 3%	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.5% ≤ ± 1.5mm	± 0.4%	Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
Rectangularity EN ISO I 0545 - 2	± 0.5% ≤ ± 2mm	± 0.4%	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Min. Class B
Surface Flatness EN ISO   0545 - 2	± 0.5% ≤ ± 2mm	± 0.4%	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Min. Class 3
Water Absorption EN ISO I 0545 - 3	≤ 0.5%	≤ 0.1%	Fire Rating	-	Class A I FL Non Combustible
kg Weight / M²	<b>22.28 kg</b> I 0.5mm thick				

Note: All products are classed as Bia - Glazed Porcelain. All products conform to BS EN 14411.

#### ${\cal D}$ Sustainability Information

Range	Material	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Zodiac	Glazed Porcelain [BIa]	Yes	Up to 30%	Up to 100% (Boxes)	Up to 100%

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Zodiac pages on our website.

<sup>\*</sup> Mosaics are suitable for internal and external wall applications only.

\*\* Only products with the Textured Structure are suitable for external floor and wet barefoot applications.

#### Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- $\bullet$  Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- $\bullet$  Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.







I www.johnson-tiles.com

# For more information about Zodiac or any of our other product ranges simply visit www.johnson-tiles.com | f ♥ ◎ P in ▶

#### Where To Find Us

Johnson Tiles Harewood Street, Tunstall, Stoke on Trent, Staffordshire.

ST6 5JZ

Tel: +44 (0)1782 575 575 Fax: +44 (0)1782 577 377 Email: info@johnson-tiles.com

#### Samples Enquiries

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379 Email: samples@johnson-tiles.com

#### Technical Helpline

Tel: +44 (0) 1782 524 111 Fax: +44 (0) 1782 577 379 Email: techadvice@johnson-tiles.com

