

# CONTEMPO

GLAZED PORCELAIN | FLOOR AND WALL TILES

MARBLE

STONE

SELECT



[www.johnson-tiles.com](http://www.johnson-tiles.com)

© 2024-25 Johnson Tiles Limited

Est. 1901  
**JOHNSON  
TILES**



# CONTEMPO



**ELEVEN COLOURS**




**THREE SIZES**



**THREE FINISHES**

Introducing Contempo, a versatile collection of contemporary marble and stone-effect wall and floor tiles, available in eleven colour-ways. This range showcases deep mineral vein detailing, chic limestone and terrazzo effects, and warm Statuario marble styles to complement any design aesthetic. Offered in large-format sizes from 600x300mm to 1200x600mm, Contempo comes in three adaptable finishes - Natural, Polished, and Grip. The Grip finish, with a PTV 36+ slip resistance rating, ensures suitability for both residential and commercial spaces, making Contempo a refined and practical choice for any project.












## COLOURS AND PRODUCT CODES


V2: Low to Moderate Shade Variation

---



### STATUARIO - WHITE MARBLE PEI: III LRV: 65

Product Code: N COT01N + P COT01P



### STATUARIO - GOLD MARBLE PEI: III LRV: 65


Product Code: N COT02N + P COT02P



## COLOURS AND PRODUCT CODES

V2: Low to Moderate Shade Variation

---




### ARMANI - PLATINUM PEI: IV LRV: 50

Product Code: G COT03G



### ARMANI - STEEL PEI: III LRV: 31

Product Code: G COT04G



### ARMANI - IRON PEI: III LRV: 24


Product Code: G COT05G



## COLOURS AND PRODUCT CODES


V2: Low to Moderate Shade Variation

---



### TERRAZZO - PEWTER PEI: IV LRV: 55

Product Code: G COT06G



### TERRAZZO - ASH PEI: III LRV: 32

Product Code: G COT07G



## COLOURS AND PRODUCT CODES

V2: Low to Moderate Shade Variation

---



### LIMESTONE - BONE PEI: IV LRV: 53

Product Code: G COT08G




### LIMESTONE - STONE PEI: III LRV: 31

Product Code: G COT09G



### LIMESTONE - FOSSIL PEI: III LRV: 24

Product Code: G COT10G




### LIMESTONE - COAL PEI: III LRV: 12

Product Code: G COT11G



## SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information



#	Size Format	Thickness	Finish	Availability	Class	Pcs / Box	M <sup>2</sup> / Box	Kg / Box
01	1200x600mm	9.2mm	Natural	See Availability Chart	Bla	2 Tiles	1.44 m <sup>2</sup>	29.50 kg
			Polished	See Availability Chart	Bla	2 Tiles	1.44 m <sup>2</sup>	29.50 kg
			Grip	See Availability Chart	Bla	2 Tiles	1.44 m <sup>2</sup>	29.50 kg
02	600x600mm	8.3mm	Natural	See Availability Chart	Bla	4 Tiles	1.44 m <sup>2</sup>	27.50 kg
			Polished	See Availability Chart	Bla	4 Tiles	1.44 m <sup>2</sup>	27.50 kg
			Grip	See Availability Chart	Bla	4 Tiles	1.44 m <sup>2</sup>	27.50 kg
03	600x300mm	8.4mm	Grip	See Availability Chart	Bla	5 Tiles	0.90 m <sup>2</sup>	18.00 kg

Availability						Size		
Colour	Colour	Code	Finish	PEI Rating	LRV Rating	1200x600mm	600x600mm	600x300mm
Statuario	White Marble	COT01N	Natural	III	65.00	•	•	
		COT01P	Polished	III	65.00	•	•	
	Gold Marble	COT02N	Natural	III	65.00	•	•	
		COT02P	Polished	III	65.00	•	•	
Armani	Platinum	COT03G	Grip	IV	50.00	•	•	
	Steel	COT04G	Grip	III	31.00	•	•	
	Iron	COT05G	Grip	III	24.00	•	•	
Terrazzo	Pewter	COT06G	Grip	IV	55.00	•	•	
	Ash	COT07G	Grip	III	32.00	•	•	
Limestone	Bone	COT08G	Grip	IV	53.00	•	•	•
	Stone	COT09G	Grip	III	31.00	•	•	•
	Fossil	COT10G	Grip	III	24.00	•	•	•
	Coal	COT11G	Grip	III	12.00	•	•	•




**Note:** Glazed Porcelain / Bla tiles. For more information please see the suitability advice given in the technical section.  
All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com). (R) Rectified Edge.






# TECHNICAL SUPPORT

## Specification, Sustainability and Important Information













### Product Specification

Range Name	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	Material / Class
Contempo	 Natural	Internal and External	Internal Only	-	Glazed Porcelain / Bla
	 Polished	Internal and External	Internal Only	-	Glazed Porcelain / Bla
	 Grip	Internal and External	Internal Only	-	Glazed Porcelain / Bla

### Floor Values

Finish	Colour	PTV (96)	PTV (55)	R 10	Wet Ramp	PEI	Traffic
 Natural	Statuario - White Marble and Statuario - Gold Marble	Wet 0 - 24	-	-	-	III	Light Commercial
 Polished	Statuario - White Marble and Statuario - Gold Marble	Wet 0 - 24	-	-	-	III	Light Commercial
 Grip	Armani - Platinum, Terrazzo - Pewter and Limestone Bone Only	Wet 36+	-	R 10	-	IV	Commercial
	All Other Colours Shown	Wet 36+	-	R 10	-	III	Light Commercial

### Physical Properties - Glazed Porcelain / Bla

Test and Standard	Requirement	Result	Test and Standard	Requirement	Result
 <b>Length / Width</b> EN ISO 10545-2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	 <b>Modulus of Rupture</b> EN ISO 10545-4	Min. 35N / mm <sup>2</sup>	Pass
 <b>Thickness</b> EN ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	 <b>Thermal Shock</b> EN ISO 10545-9	Pass	Pass
 <b>Straightness of Side</b> EN ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	 <b>Frost Resistance</b> EN ISO 10545-12	Resistant	Resistant
 <b>Rectangularity</b> EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 <b>Chemical Resistance</b> EN ISO 10545-13	Min. Class B	Pass
 <b>Surface Flatness</b> EN ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 <b>Stain Resistance</b> EN ISO 10545-14	Min. Class 3	Pass
 <b>Water Absorption</b> EN ISO 10545-3	$\leq 0.5\%$	Pass	 <b>Fire Rating</b>		Class A I FL Non Combustible

### Sustainability Credentials

Range Name	Material / Class	EPD	Recycled Content - Tiles	Recycled Content - Packaging
Contempo	Glazed Porcelain / Bla	-	Up to 10%	Up to 100% (Boxes Only)

**Note:** Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All floor tiles shown in this literature achieve a PTV (96) Dry 36+ test result. PTV (96): Pendulum Test Value - 45. PTV (55): Pendulum Test Value - TRL. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

### Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com)

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524111 or email: [technical@johnson-tiles.com](mailto:technical@johnson-tiles.com).



## WHERE TO FIND US

### Head Office

Harewood Street, Tunstall,  
Stoke on Trent, Staffordshire,  
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575  
Email: [info@johnson-tiles.com](mailto:info@johnson-tiles.com)  
[www.johnson-tiles.com](http://www.johnson-tiles.com)

---

### Material Lab Studio

10 Great Titchfield Street,  
London, W1W 8BB,  
United Kingdom

Tel: +44 (0)20 7436 8629  
Email: [info@material-lab.co.uk](mailto:info@material-lab.co.uk)  
[www.material-lab.co.uk](http://www.material-lab.co.uk)

---

### Factory Outlet

Tel: +44 (0)1782 524 040  
Email: [foutlet@johnson-tiles.com](mailto:foutlet@johnson-tiles.com)  
[www.outlet.johnson-tiles.com](http://www.outlet.johnson-tiles.com)

---

### Customer Services

Tel: +44 (0)1782 524 000  
Email: [sales@johnson-tiles.com](mailto:sales@johnson-tiles.com)  
8:30am - 4:30pm (Monday - Friday)

---

### Order A Sample

Tel: +44 (0)1782 524 043  
Email: [samples@johnson-tiles.com](mailto:samples@johnson-tiles.com)

---

### Technical Advice Helpline

Tel: +44 (0)1782 524 111  
Email: [technical@johnson-tiles.com](mailto:technical@johnson-tiles.com)

---

Updated: May 2025