

GLIDE

GLAZED CERAMIC & PORCELAIN | FLOOR & WALL TILES

MARBLE EFFECT TILES [SELECT](#)



JOHNSON • TILES 

MADE IN THE UK SINCE 1901

GLIDE

With the calming, neutral tone of pure white threaded with the gentle veining of carrara marble, Glide proves that simplicity can still make a big impact. Understated and elegant, Glide showcases calm serenity with a timeless finish, expanding the limits of any space with an airy, light, bright feel. With the linear structured décor options providing textural definition, this range delivers clean, sleek looks, bringing sophistication and style to any setting.

Front Cover Image: White Carrara Gloss 600x300mm - GLD02A, White Carrara Linear Structure Gloss 600x300mm - GLD02D & White Carrara Polished 600x600mm - GLD01P




White Carrara Matt 600x600mm - GLD01N



Roomset Photography



White Carrara Gloss 600x300mm - GLD02A
White Carrara Polished 600x600mm - GLD01P



White Carrara Matt 600x300mm - GLD01A
White Carrara Linear Structure Matt 600x300mm - GLD01D



Colours & Product Codes

VI: Low Shade Variation



WHITE CARRARA

[M] GLD01A LRV: 64
+
[G] GLD02A LRV: 72



WHITE CARRARA LINEAR STRUCTURE

[M] GLD01D LRV: 64
+
[G] GLD02D LRV: 72




WHITE CARRARA

[M] GLD01N PEI: IV LRV: 64
+
[P] GLD01P PEI: IV LRV: 72



Sizes, Finishes & Availability





#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	600x600mm	[M] Matt	White Carrara	9.4mm	3 Tiles	1.08 m ²	23.00 kg
		[P] Polished	White Carrara	9.4mm	3 Tiles	1.08 m ²	23.00 kg
2	600x300mm	[M] Matt	White Carrara	9mm	7 Tiles	1.26 m ²	18.50 kg
		[G] Gloss	White Carrara	9mm	7 Tiles	1.26 m ²	18.50 kg
3	600x300mm Linear Structure	[M] Matt	White Carrara	9mm	7 Tiles	1.26 m ²	18.50 kg
		[G] Gloss	White Carrara	9mm	7 Tiles	1.26 m ²	18.50 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website.
All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value. ® Rectified Edge





Technical Data

Specification














Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Glide	600x300x10mm	Internal Only	-	-	VI	Glazed Ceramic [BIII]
Glide	600x600x9.4mm 	Internal & External	Internal Only	-	VI	Glazed Porcelain [Bla]
Glide	600x600x9.4mm 	Internal & External	Internal Only	-	VI	Glazed Porcelain [Bib]

Floor Values

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
 Matt	White Carrara	Dry 36+ Wet 0 - 24	-	-	-	IV	Commercial
 Polished	White Carrara	Dry 36+ Wet 0 - 24	-	-	-	IV	Commercial














Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. PTV: Pendulum Test Value.

Physical Properties - Glazed Ceramic (BIII)

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
 Length / Width EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm ²	Pass
 Thickness EN ISO 10545 - 2	$\pm 10\% \leq \pm 0.5\text{mm}$	Pass	 Thermal Shock EN ISO 10545 - 9	Pass	Pass
 Straightness of Side EN ISO 10545 - 2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	Pass	 Frost Resistance EN ISO 10545 - 12	-	Not Suitable
 Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Chemical Resistance EN ISO 10545 - 13	Min. Class B	Pass
 Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	 Stain Resistance EN ISO 10545 - 14	Min. Class 3	Pass
 Water Absorption EN ISO 10545 - 3	10% to 20%	Pass	 Fire Rating	-	Class A I Non Combustible
 Weight / M²	18.50 kg 9mm thick				














Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

Physical Properties - Glazed Porcelain (Bla)

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
 Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	$\pm 0.1\%$	 Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm ²	$\geq 37\text{N} / \text{mm}^2$
 Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	$\pm 2.5\%$	 Thermal Shock EN ISO 10545 - 9	Pass	Pass
 Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	$\pm 0.1\%$	 Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
 Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.1\%$	 Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A
 Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.2\%$	 Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 5
 Water Absorption EN ISO 10545 - 3	$\leq 0.5\%$	$\leq 0.1\%$	 Fire Rating	-	Class A I _{FL} Non Combustible
 Weight / M²	23.00 kg 9.4mm thick				

Note: All products are classed as Bla - Glazed Porcelain. All products conform to BS EN 14411.

Physical Properties - Glazed Porcelain (B1b)

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
 Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	$\pm 0.1\%$	 Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm ²	$\geq 43\text{N} / \text{mm}^2$
 Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	$\pm 2.5\%$	 Thermal Shock EN ISO 10545 - 9	Pass	Pass
 Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	$\pm 0.1\%$	 Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
 Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.1\%$	 Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A
 Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 0.5\text{mm}$	$\pm 0.2\%$	 Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 5
 Water Absorption EN ISO 10545 - 3	0.5% to 3%	1.6%	 Fire Rating	-	Class A I _{FL} Non Combustible
 Weight / M²	21.25 kg 9.4mm thick				

Note: All products are classed as B1b - Glazed Porcelain. All products conform to BS EN 14411.

Sustainability Information

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD	SKA Rating
Glide	Glazed Ceramic [BIII]	Up to 50%	Up to 100% (Boxes)	Up to 100% (Boxes)	Yes	-
Glide	Glazed Porcelain [BIa]	Up to 40%	Up to 100% (Boxes)	Up to 100% (Boxes)	Yes	-
Glide	Glazed Porcelain [B1b]	Up to 40%	Up to 100% (Boxes)	Up to 100% (Boxes)	Yes	-

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Glide pages on our website.

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.



White Carrara Matt 600x600mm - GLD01N

For more information about Glide or any
of our other product ranges simply visit
www.johnson-tiles.com |      

Where To Find Us

Johnson Tiles

Harewood Street,
Tunstall,
Stoke on Trent,
Staffordshire,
ST6 5JZ

Tel: +44 (0)1782 575 575
Fax: +44 (0)1782 577 377
Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043
Fax: +44 (0)1782 577 379
Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111
Fax: +44 (0)1782 577 379
Email: techadvice@johnson-tiles.com

Launched: March 2019 Updated: January 2021

JOHNSON • TILES 
MADE IN THE UK SINCE 1901