

# ALLURE

GLAZED PORCELAIN & CERAMIC | FLOOR & WALL TILES

MARBLE SELECT



JOHNSON • TILES

MADE IN THE UK SINCE 1901



# ALLURE



8 SIZES



1 COLOUR



2 FINISHES

A sumptuous, eye-catching range of glazed porcelain and ceramic wall and floor tiles, Allure showcases a beautiful warm carrara marble effect in two stunning finishes. Contemporary décors of on-trend star and chevron shapes provide luxurious motifs for this classic marble range, keying into the ever-popular trend for geometric designs. Ranging from wall tile options in a slim 600x300mm size to the elongated format of 2600x1200mm, Allure offers a variety of sleek size options for modern interior commercial spaces.





White/Gold Polished 2600x1200x7mm - ALL01P  
White/Gold Polished 1200x1200x9.3mm - ALL01P



White/Gold Gloss 600x300x11mm - ALL01A  
 White/Gold Weave Structure Gloss 600x300x11mm - ALL01W





White/Gold Polished 600x600x9.3mm - ALL01P



White/Gold Polished 1600x800x9.7mm - ALL01P  
 White/Gold Polished 800x800x9.7mm - ALL01P



## Size Formats Sizing & Packing Information



#	Size	Thickness	Finish	Structure	Colour Availability	Pcs / Box	M2 / Box	Kg / Box
1	2600x1200mm	7mm	<b>P</b> Polished	-	All Colours	1 Tile	3.12m <sup>2</sup>	52.00kg
2	1600x800mm	9.7mm	<b>P</b> Polished	-	All Colours	1 Tile	1.28m <sup>2</sup>	29.00kg
3	1200x1200mm	9.3mm	<b>P</b> Polished	-	All Colours	1 Tile	1.44m <sup>2</sup>	31.00kg
4	1200x600mm	9.3mm	<b>P</b> Polished	-	All Colours	2 Tiles	1.44m <sup>2</sup>	31.00kg
5	800x800mm	9.7mm	<b>P</b> Polished	-	All Colours	2 Tiles	1.28m <sup>2</sup>	27.00kg
6	600x600mm	9.3mm	<b>P</b> Polished	-	All Colours	3 Tiles	1.08m <sup>2</sup>	24.00kg

7	1200x400mm	11mm	<b>G</b> Gloss	-	All Colours	3 Tiles	1.44m <sup>2</sup>	28.00kg
				Weave	All Colours	3 Tiles	1.44m <sup>2</sup>	28.00kg
				Chevron	All Colours	3 Tiles	1.44m <sup>2</sup>	28.00kg
				Star	All Colours	3 Tiles	1.44m <sup>2</sup>	28.00kg
8	600x300mm	9mm	<b>G</b> Gloss	-	All Colours	7 Tiles	1.26m <sup>2</sup>	18.50kg
				Weave	All Colours	7 Tiles	1.26m <sup>2</sup>	18.50kg

#	Fitting	Thickness	Finish	Structure	Colour Availability	Pcs / Box	LM / Box	Kg / Box
1	600x100mm Round Top Skirting	10mm	<b>P</b> Polished	-	All Colours	15 Tiles	9.00lm	21.00kg

**Note:** All sizes indicated are metric modular. All sizes shown are nominal. (R) Rectified Edge.  
For the most up-to-date product availability information for this range, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com)





## Colours & Product Codes

V2: Low to Moderate Shade Variation



**WHITE / GOLD** (LRV: 80) (PEI: IV)

Product Codes (Bla): (P) ALL01P | Fitting Codes (Bla): (P) ALL1PS



**WHITE / GOLD** (LRV: 80)

Product Codes (BIII) Wall Tiles Only: (G) ALL01A



**WHITE / GOLD WEAVE STRUCTURE** (LRV: 80)

Product Codes (BIII) Wall Tiles Only: (G) ALL01W



**WHITE / GOLD CHEVRON STRUCTURE** (LRV: 80)

Product Codes (BIII) Wall Tiles Only: (G) ALL01V



**WHITE / GOLD STAR STRUCTURE** (LRV: 80)

Product Codes (BIII) Wall Tiles Only: (G) ALL01S



## Technical, Sustainability & Important Information

### Specification

Range	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Allure	Polished	Internal & External	Internal Only	-	V2	Glazed Porcelain (Bla)
	Gloss	Internal Only	-	-	V2	Glazed Ceramic (BIII)

### Floor Values

Finish	Structure	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
Polished	-	White / Gold	Dry 36+ Wet 0 - 24	-	-	-	IV	Commercial

### Physical Properties - Glazed Porcelain (Bla)

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm <sup>2</sup>	Pass
Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Pass
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Pass
Water Absorption EN ISO 10545 - 3	$\leq 0.5\%$	Pass	Fire Rating	-	Class A I Fl. Non Combustible
Weight / M <sup>2</sup>	22.66kg 9.7mm thick	21.53kg 9.3mm thick	16.67 kg 7mm thick		

### Physical Properties - Glazed Ceramic (BIII)

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm <sup>2</sup>	Pass
Thickness EN ISO 10545 - 2	$\pm 10\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545 - 12		Not Suitable
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Pass
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Pass
Water Absorption EN ISO 10545 - 3	10% to 20%	Pass	Fire Rating	-	Class A I Non Combustible
Weight / M <sup>2</sup>	19.46kg 11mm thick	14.73kg 9mm thick			

### Sustainability Information

Range	Material	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Allure	Glazed Porcelain (Bla)	Yes	Up to 40%	Up to 100% (Boxes)	Up to 100% (Boxes)
	Glazed Ceramic (BIII)	Yes	Up to 40%	Up to 100% (Boxes)	Up to 100% (Boxes)

**Note:** Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All glazed porcelain (Bla) and glazed ceramic (BIII) products listed conform to BS EN 14411. CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. For a full overview of our environmental credentials please visit [www.johnson-tiles.com/about/sustainability](http://www.johnson-tiles.com/about/sustainability). EPD: Environmental Product Declaration.

## Technical, Sustainability & Important Information

### Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles, several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed. For a comprehensive colour, size and finish overview along with full technical and sustainability information for all of the product shown in this product presenter, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com).

- All sizes shown are metric modular.
- For specific suitability details please contact our technical department.
- Johnson Tiles cannot accept responsibility for tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does/will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2022 Johnson Tiles. All rights reserved.



All product technical values quoted in this product presenter are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles are British Standard registered and all products conform to the standards set in BS EN 14411.

For the reassurance of single-source supply, Johnson Tiles offers a free of charge NBS M40 specification writing service featuring the Norcros Adhesives range of tile fixing products. To find out more or for any questions or queries relating to any tile related technical information featured in this product presenter, please contact our technical advice helpline on +44 (0) 1782 524 111 or email [ddunlop@johnson-tiles.com](mailto:ddunlop@johnson-tiles.com)

The colours shown in this sample tile wallet and attached booklet are as accurate as printing processes will allow. Please refer to actual product samples before specifying. Every effort has been made to ensure the accuracy of the information given.



White/Gold Polished | 200x600x9.3mm - ALL01P  
White/Gold Polished | 200x1200x9.3mm - ALL01P

For more information about **Allure** or any of our other product ranges simply visit

[www.johnson-tiles.com](http://www.johnson-tiles.com) | [f](#) [t](#) [i](#) [p](#) [in](#) [v](#)

#### Where To Find & Contact Us

##### Johnson Tiles Head Office

Harewood Street, Tunstall,  
Stoke on Trent, Staffordshire,  
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575  
Email: [info@johnson-tiles.com](mailto:info@johnson-tiles.com)  
[www.johnson-tiles.com](http://www.johnson-tiles.com)

---

##### Material Lab Studio

10 Great Titchfield Street,  
London, W1W 8BB,  
United Kingdom

Tel: +44 (0)20 7436 8629  
Email: [info@material-lab.co.uk](mailto:info@material-lab.co.uk)  
[www.material-lab.co.uk](http://www.material-lab.co.uk)

---

##### Johnson Tiles Factory Outlet

Tel: +44 (0)1782 524 040  
Email: [foutlet@johnson-tiles.com](mailto:foutlet@johnson-tiles.com)  
[www.outlet.johnson-tiles.com](http://www.outlet.johnson-tiles.com)

---

##### Customer Services

Tel: +44 (0)1782 524 000  
Email: [sales@johnson-tiles.com](mailto:sales@johnson-tiles.com)

---

##### Order A Sample

Tel: +44 (0)1782 524 043  
Email: [samples@johnson-tiles.com](mailto:samples@johnson-tiles.com)

---

##### Technical Advice

Tel: +44 (0)1782 524 111  
Email: [ddunlop@johnson-tiles.com](mailto:ddunlop@johnson-tiles.com)

---

Launched: March 2022 / Updated: January 2023

**JOHNSON • TILES**   
MADE IN THE UK SINCE 1901

Johnson Tiles is a division of Norcross Group (Holdings) Limited,  
Ladyfield House, Station Road, Wilmslow, Cheshire, SK9 1BU,  
United Kingdom. Registered in England number 566694.