









Studio offers a warm colour palette with base tones of cream, white and sand. The Gloss finish reflects light for a modern look, while the Satin options are more delicate. Try pairing with the complementary scored or linear structure options to create a design feature or use on their own for a statement finish. Bordered options are also available to complete the look. Front Cover Image: Haze Linear Structure Satin 360x275mm - STUD2L







TUNDRA G TUNDIA + S TUND2A LRV. 83



TUNDRA SCOREDS TUND2ELRV: 83



TUNDRA LINEAR STRUCTURE S TUND2L LRV: 83



HAZE G STUD2G + S STUD2S LRV: 63



HAZE SCORED



HAZE LINEAR STRUCTURE (S) STUD2L (LRV: 63)



S STUDIB LRV: ??



SAND G STUD3G + S STUD3S LRV: 40



S STUD3E LRV: 40



SAND LINEAR STRUCTURE S STUD3L LRV: 40



LINEAR STRUCTURE (S) STUD2B LRV: ??



MIST G STUD4G + S STUD4S LRV: 42




MIST SCORED S STUD4E LRV: 42



MIST LINEAR STRUCTURE S STUD4L LRV: 42





#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
I	360x275mm	G Gloss	Tundra, Haze, Sand & Mist Only	8mm	10 Tiles	0.99 m²	14.00 kg
		s Satin	Tundra, Haze, Sand & Mist Only	8mm	I 0 Tiles	0.99 m²	14.00 kg
2	360x275mm Scored	S Satin	Tundra, Haze, Sand & Mist Only	8mm	10 Tiles	0.99 m²	14.00 kg
3	360x275mm Linear Structure	S Satin	Tundra, Haze, Sand & Mist Only	8mm	10 Tiles	0.99 m²	14.00 kg
4	360x50mm Linear Structure	S Satin	Beige Mix & Grey Mix Only	5mm	5 Tiles	1.80 lm	1.60 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.



Technical Data

Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Studio	All Sizes Shown	Internal Only	-	-	VI	Glazed Ceramic [BIII]

Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	≤ ± 0.25%	Modulus of Rupture EN ISO 10545 - 4	Min. I 5N / mm²	≥ 25N / mm²
Thickness EN ISO 10545 - 2	± 10% ≤ ± 0.5mm	± 2.5%	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	± 0.15%	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.4%	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A – B
Surface Flatness EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.3%	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	15% to 17%	Fire Rating	-	Class A I Non Combustible
kg Weight / M ²	14.10 kg 8mm thick				

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

${\cal O}$ Sustainability Information

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD
Studio	Glazed Ceramic [BIII]	Up to 20%	Up to 100%	Up to 100%	Yes

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Studio pages on our website.

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

• All sizes shown are metric modular.

- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.



ISC

For more information about Studio or any of our other product ranges simply visit www.johnson-tiles.com | f ♥ @ ? in ▷

Where To Find Us

Johnson Tiles Harewood Street, Tunstall, Stoke on Trent, Staffordshire, ST6 5JZ

Tel: +44 (0)1782 575 575 Fax: +44 (0)1782 577 377 Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043 Fax: +44 (0)1782 577 379 Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111 Fax: +44 (0)1782 577 379 Email: techadvice@johnson-tiles.com

Launched: October 2015 Updated: February 2023

