

COAST

UN-GLAZED PORCELAIN | FLOOR & WALL TILES

STONE SELECT



JOHNSON • TILES 

MADE IN THE UK SINCE 1901

COAST



7 SIZES




5 COLOURS



2 FINISHES

Coast is a stone-effect range creating visual interest through its speckled conglomerate design. The five architectural tones of Ivory, Beige, Grey, Taupe, and Charcoal form a contemporary colour palette ideal for commercial spaces. Two finishes are available with the Bush Hammered option providing a PTV slip resistance rating of 36+, ideal for wet barefoot applications. All field tiles within this range feature rectified edges for precision fixing.





Ivory Bush Hammered 600x600x10.5mm - CST01B
Charcoal Natural 600x600x10.5mm - CST05N



Taupe Natural 600x600x10.5mm - CST04N




Beige Natural 890x890x10.5mm - CST02N



Grey Natural 1190x600x10.5mm - CST03N



Size Formats Sizing & Packing Information



#	Size	Thickness	Finish	Structure	Colour Availability	Pcs / Box	M ² / Box	Kg / Box
1	1190x600mm	10.5mm	(N) Natural	-	All Colours	2 Tiles	1.43m ²	34.79kg
			(B) Bush Hammered	-	All Colours	2 Tiles	1.43m ²	34.79kg
2	890x890mm	10.5mm	(N) Natural	-	All Colours	2 Tiles	1.59m ²	38.71kg
			(B) Bush Hammered	-	All Colours	2 Tiles	1.59m ²	38.71kg
3	600x600mm	10.5mm	(N) Natural	-	All Colours	3 Tiles	1.08m ²	24.40kg
			(B) Bush Hammered	-	All Colours	3 Tiles	1.08m ²	24.40kg
4	600x300mm	10.5mm	(N) Natural	-	All Colours	5 Tiles	0.90m ²	20.29kg
			(B) Bush Hammered	-	All Colours	5 Tiles	0.90m ²	20.29kg
5	300x300mm (50x50mm) Square Mosaic	10.5mm	(N) Natural	-	All Colours	8 Sheets	0.72m ²	17.50kg
6	300x300mm (150x50mm) Strip Mosaic	10.5mm	(N) Natural	-	All Colours	8 Sheets	0.72m ²	17.50kg
7	300x300mm (300x50mm) Strip Mosaic	10.5mm	(N) Natural	-	All Colours	8 Sheets	0.72m ²	17.50kg

#	Fitting	Thickness	Finish	Structure	Colour Availability	Pcs / Box	LM / Box	Kg / Box
8	890x70mm Round Top Skirting	10.5mm	(N) Natural	-	All Colours	12 Tiles	10.68lm	18.00kg
9	600x70mm Round Top Skirting	10.5mm	(N) Natural	-	All Colours	18 Tiles	10.80lm	18.00kg

Note: All sizes indicated are metric modular. All sizes shown are nominal. (R) Rectified Edge.
For the most up-to-date product availability information for this range, please visit our website - www.johnson-tiles.com



Ivory Bush Hammered 600x600x10.5mm - CST01B



Colours & Product Codes

V4: High Shade Variation



IVORY LRV: 57

Product Codes: N CST01N + B CST01B | Mosaic Codes: N CST1NM | Fitting Codes: N CTS1NS



BEIGE LRV: 53

Product Codes: N CST02N + B CST02B | Mosaic Codes: N CST2NM | Fitting Codes: N CTS2NS



GREY LRV: 38

Product Codes: N CST03N + B CST03B | Mosaic Codes: N CST3NM | Fitting Codes: N CTS3NS



Colours & Product Codes

V4: High Shade Variation




TAUPE LRV: 31

Product Codes: (N) CST04N + (B) CST04B | Mosaic Codes: (N) CST4NM | Fitting Codes: (N) CTS4NS



CHARCOAL LRV: 16

Product Codes: (N) CST05N + (B) CST05B | Mosaic Codes: (N) CST5NM | Fitting Codes: (N) CTS5NS



Grey Natural | 190x600x10.5mm - CST03N



Technical, Sustainability & Important Information

Specification

Range	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Coast	N Natural	Internal & External	Internal Only	-	V4	Un-glazed Porcelain (Bla)
	B Bush Hammered	Internal & External	Internal & External	Yes	V4	Un-glazed Porcelain (Bla)

Floor Values

Finish	Structure	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
N Natural	-	All Colours	Dry 36+ Wet 36+	-	R10	B	-	Commercial
B Bush Hammered	-	All Colours	Dry 36+ Wet 36+	Wet 36+	R12	C	-	Commercial

Physical Properties

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm ²	$\geq 45\text{N} / \text{mm}^2$
Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	$\pm 3\%$	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	$\pm 0.3\%$	Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 5
Water Absorption EN ISO 10545 - 3	$\leq 0.5\%$	$\leq 0.1\%$	Fire Rating	-	Class A I _{fl} Non Combustible
Weight / M ²	22.60kg 10.5mm thick				

Sustainability Information

Range	Material	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Coast	Un-glazed Porcelain (Bla)	Yes	Up to 10%	Up to 100% (Boxes)	Up to 100%

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications.

Please contact our technical helpline, or visit our website for specification and installation advice. All un-glazed porcelain (Bla) products listed conform to BS EN 14411.

CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute.

For a full overview of our environmental credentials please visit www.johnson-tiles.com/about/sustainability. EPD: Environmental Product Declaration.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed. For a comprehensive colour, size and finish overview along with full technical and sustainability information for all of the product shown in this product presenter, please visit our website - www.johnson-tiles.com.

- All sizes shown are metric modular.
- For specific suitability details please contact our technical department.
- Johnson Tiles cannot accept responsibility for tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does/will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2022 Johnson Tiles. All rights reserved.



All product technical values quoted in this product presenter are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles are British Standard registered and all products conform to the standards set in BS EN 14411.

For the reassurance of single-source supply, Johnson Tiles offers a free of charge NBS M40 specification writing service featuring the Norcros Adhesives range of tile fixing products. To find out more or for any questions or queries relating to any tile related technical information featured in this product presenter, please contact our technical advice helpline on +44 (0) 1782 524 111 or email ddunlop@johnson-tiles.com

The colours shown in this sample tile wallet and attached booklet are as accurate as printing processes will allow. Please refer to actual product samples before specifying. Every effort has been made to ensure the accuracy of the information given.

For more information about Coast or any
of our other product ranges simply visit

www.johnson-tiles.com | [f](#) [t](#) [i](#) [p](#) [in](#) [v](#)

Where To Find & Contact Us

Johnson Tiles Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Johnson Tiles Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice

Tel: +44 (0)1782 524 111
Email: ddunlop@johnson-tiles.com

Launched: March 2022

JOHNSON • TILES 
MADE IN THE UK SINCE 1901

Johnson Tiles is a division of Norcross Group (Holdings) Limited,
Ladyfield House, Station Road, Wilmslow, Cheshire, SK9 1BU,
United Kingdom. Registered in England number 566694.