

# JIVE

GLAZED PORCELAIN | FLOOR & WALL TILES

CONCRETE

ABSOLUTE





# JIVE



**FOUR COLOURS**



**FOUR SIZES**



**ONE FINISH**

Jive is a collection of porcelain floor and wall tiles featuring an uncomplicated palette of neutral colours – Bone, Silver, Pebble and Steel – offering a softer and more subtle approach to the industrial trend. With a selection of co-ordinating sizes and fittings available, starting at 600x300mm and 600x600mm, going up to 900x900mm and 1200x600mm, with all size-formats including rectified edges, making them perfect for precise installations. An elegant Natural finish is available across all size and colour options, which achieves a PTV 36+ slip rating; try blending the tones and sizes from across the range for a sleek, contemporary look.







Silver Natural 600x300x7.8mm - JIV02N  
Steel Natural 600x600x7.8mm - JIV04N



Pebble Natural 600x300x7.8mm - JIV03N





## Colours & Product Codes

V3: Moderate to High Shade Variation



**BONE** LRV: 45 PEI: IV

Product Code - All Sizes: **N** JIV01N | Fitting Code - All Skirtings: **N** JIV1NS



**SILVER** LRV: 42 PEI: IV


Product Code - All Sizes: **N** JIV02N | Fitting Code - All Skirtings: **N** JIV2NS





## Colours & Product Codes

V3: Moderate to High Shade Variation



**PEBBLE** LRV: 37 PEI: IV

Product Code - All Sizes: **N** JIV03N | Fitting Code - All Skirtings: **N** JIV3NS



**STEEL** LRV: 32 PEI: IV


Product Code - All Sizes: **N** JIV04N | Fitting Code - All Skirtings: **N** JIV4NS





## Size Formats

### Sizing & Packing Information



#	Size	Thickness	Finish	Structure	Class	Pcs / Box	M2 / Box	Kg / Box
1	1200x600mm	8.8mm	(N) Natural	-	Bla	2 Tiles	1.44 m <sup>2</sup>	35.00 kg
2	900x900mm	9.5mm	(N) Natural	-	Bla	2 Tiles	1.60 m <sup>2</sup>	38.00 kg
3	600x600mm	7.8mm	(N) Natural	-	Bla	4 Tiles	1.44 m <sup>2</sup>	24.50 kg
4	600x300mm	7.8mm	(N) Natural	-	Bla	7 Tiles	1.26 m <sup>2</sup>	21.00 kg

#	Fitting	Thickness	Finish	Structure	Class	Pcs / Box	LM / Box	Kg / Box
5	1200x90mm Round Top Skirting	8.8mm	(N) Natural	-	Bla	10 Tiles	12.00 Lm	25.00 kg
6	900x90mm Round Top Skirting	9.5mm	(N) Natural	-	Bla	12 Tiles	10.80 Lm	23.00 kg
7	600x90mm Round Top Skirting	7.8mm	(N) Natural	-	Bla	16 Tiles	9.60 Lm	16.00 kg

**Note:** (R) Rectified Edge. Class Bla: Glazed Porcelain Tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com).



Steel Natural 600x300x7.8mm & 600x600x7.8mm - JIV04N





## Technical, Sustainability & Important Information

### Specification

Range	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material / Class
Jive	Natural	Internal & External	Internal Only	-	V3	Glazed Porcelain [Bla]

### Floor Values

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
Natural	All Colours	Dry 36+ Wet 36+	-	R10	-	IV	Commercial

### Physical Properties

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result
<b>Length / Width</b> EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	<b>Modulus of Rupture</b> EN ISO 10545 - 4	Min. 35N / mm <sup>2</sup>	Pass
<b>Thickness</b> EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	<b>Thermal Shock</b> EN ISO 10545 - 9	Pass	Pass
<b>Straightness of Side</b> EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	<b>Frost Resistance</b> EN ISO 10545 - 12	Resistant	Resistant
<b>Rectangularity</b> EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	<b>Chemical Resistance</b> EN ISO 10545 - 13	Min. Class B	Class A
<b>Surface Flatness</b> EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	<b>Stain Resistance</b> EN ISO 10545 - 14	Min. Class 3	Class 4
<b>Water Absorption</b> EN ISO 10545 - 3	$\leq 0.5\%$	Pass	<b>Fire Rating</b>	-	Class A1 <sup>FL</sup> Non Combustible
<b>Weight / M<sup>2</sup></b>	17.01 kg 7.8mm thick	24.31 kg 8.8mm thick	21.88 kg 9.5mm thick		

### Sustainability Information

Range	Material / Class	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Jive	Glazed Porcelain [Bla]	-	Up to 30%	Some Part Recycled	Up to 100%

**Note:** Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications.

Please contact our technical helpline for specification and installation advice. All glazed porcelain [Bla] products shown in this range overview conform to BS EN 14411.

CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097).

PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. For a full company sustainability overview please visit [www.johnson-tiles.com/about/sustainability](http://www.johnson-tiles.com/about/sustainability).

### Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed. For a comprehensive colour, size and finish overview along with full technical and sustainability information for all of the product shown in this product presenter, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com).

- All sizes shown are metric modular.
- For specific suitability details please contact our technical department.
- Johnson Tiles cannot accept responsibility for tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does/will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2023 Johnson Tiles. All rights reserved.



All product technical values quoted in this product presenter are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles are British Standard registered and all products conform to the standards set in BS EN 14411.

For the reassurance of single-source supply, Johnson Tiles offers a free of charge NBS M40 specification writing service featuring the Norcros Adhesives range of tile fixing products. To find out more or for any questions or queries relating to any tile related technical information featured in this product presenter, please contact our technical advice helpline on +44 (0)1782 524 111 or email [ddunlop@johnson-tiles.com](mailto:ddunlop@johnson-tiles.com)

The colours shown in this sample tile wallet and attached booklet are as accurate as printing processes will allow. Please refer to actual product samples before specifying. Every effort has been made to ensure the accuracy of the information given.



For more information about **Jive** or any  
of our other product ranges simply visit  
**www.johnson-tiles.com** |      

#### Where To Find & Contact Us

##### Johnson Tiles Head Office

Harewood Street, Tunstall,  
Stoke on Trent, Staffordshire,  
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575  
Email: [info@johnson-tiles.com](mailto:info@johnson-tiles.com)  
[www.johnson-tiles.com](http://www.johnson-tiles.com)

##### Material Lab Studio

10 Great Titchfield Street,  
London, W1W 8BB,  
United Kingdom

Tel: +44 (0)20 7436 8629  
Email: [info@material-lab.co.uk](mailto:info@material-lab.co.uk)  
[www.material-lab.co.uk](http://www.material-lab.co.uk)

##### Johnson Tiles Factory Outlet

Tel: +44 (0)1782 524 040  
Email: [foutlet@johnson-tiles.com](mailto:foutlet@johnson-tiles.com)  
[www.outlet.johnson-tiles.com](http://www.outlet.johnson-tiles.com)

##### Customer Services

Tel: +44 (0)1782 524 000  
Email: [sales@johnson-tiles.com](mailto:sales@johnson-tiles.com)

##### Order A Sample

Tel: +44 (0)1782 524 043  
Email: [samples@johnson-tiles.com](mailto:samples@johnson-tiles.com)

##### Technical Advice

Tel: +44 (0)1782 524 111  
Email: [ddunlop@johnson-tiles.com](mailto:ddunlop@johnson-tiles.com)

Launched: May 2023

[www.johnson-tiles.com](http://www.johnson-tiles.com) |      

**JOHNSON • TILES**   
MADE IN THE UK SINCE 1901

Johnson Tiles is a division of Norcros Group (Holdings) Limited,  
Ladyfield House, Station Road, Wilmslow, Cheshire, SK9 1BU,  
United Kingdom. Registered in England number 566694.