

# KOTTO

GLAZED PORCELAIN | FLOOR AND WALL TILES

STONE ABSOLUTE



[www.johnson-tiles.com](http://www.johnson-tiles.com)

© 2024 Johnson Tiles Limited

Est. 1901  
**JOHNSON  
TILES**

# KOTTO



FOUR COLOURS



THREE SIZES



TWO FINISHES

Inspired by the cotto trend, our Kotto collection displays classic terracotta tones, complimented by warm neutral shades for a complete offer. Available in White, Beige, Grey and Red, this stone-effect range of tiles has a rustic charm, which can be carried through from floor to wall and indoor to outdoor. Three versatile sizes can be used alone or together for a truly unique look, along with the co-ordinating skirting options. Presented in a Natural or Grip finish, the latter with a PTV 36+ slip resistance rating ideal for wet barefoot applications.





Grey Natural 455x455x8mm - KOT03N

## COLOURS AND PRODUCT CODES

V4: High Shade Variation

---



**WHITE** PEI: IV LRV: 54

Product Code:  KOT01N +  KOT01G | Fitting Code:  KOT1NS



**BEIGE** PEI: III LRV: 31

Product Code:  KOT02N +  KOT02G | Fitting Code:  KOT2NS

## COLOURS AND PRODUCT CODES

V4: High Shade Variation

---



**GREY** PEI: III LRV: 38

Product Code:  KOT03N +  KOT03G | Fitting Code:  KOT3NS




**RED** PEI: II LRV: 30

Product Code:  KOT04N +  KOT04G | Fitting Code:  KOT4NS

# SIZE FORMATS AND AVAILABILITY

Size Options and Packing Information



| #  | Size Format | Thickness | Finish  | Availability      | Class | Pcs / Box | M <sup>2</sup> / Box | Kg / Box |
|----|-------------|-----------|---------|-------------------|-------|-----------|----------------------|----------|
| 01 | 605x305mm   | 7.8mm     | Natural | All Colours Shown | Bla   | 8 Tiles   | 1.47 m <sup>2</sup>  | 24.84 kg |
| 02 | 455x455mm   | 8mm       | Natural | All Colours Shown | Bla   | 6 Tiles   | 1.24 m <sup>2</sup>  | 22.80 kg |
| 03 | 330x330mm   | 7.2mm     | Natural | All Colours Shown | Bla   | 10 Tiles  | 1.09 m <sup>2</sup>  | 17.20 kg |
|    |             |           | Grip    | All Colours Shown | Bla   | 10 Tiles  | 1.09 m <sup>2</sup>  | 17.20 kg |

| #  | Fittings                 | Thickness | Finish  | Availability      | Class | Pcs / Box | Lm / Box | Kg / Box |
|----|--------------------------|-----------|---------|-------------------|-------|-----------|----------|----------|
| 05 | 605x80mm<br>R/T Skirting | 7.8mm     | Natural | All Colours Shown | Bla   | 13 Tiles  | 7.86 Lm  | 10.60 kg |
| 06 | 455x80mm<br>R/T Skirting | 8mm       | Natural | All Colours Shown | Bla   | 32 Tiles  | 15.56 Lm | 19.42 kg |
| 07 | 330x80mm<br>R/T Skirting | 7.2mm     | Natural | All Colours Shown | Bla   | 25 Tiles  | 8.25 Lm  | 9.75 kg  |

**Note:** Glazed Porcelain / Bla tiles. For more information please see the suitability advice given in the technical section. All sizes indicated are metric modular. All sizes shown are nominal. For the most up-to-date size, colour and finish availability, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com).





White Natural 605x305x7.8mm - KOT01N



# TECHNICAL SUPPORT

Specification, Sustainability and Important Information













## Product Specification

| Range Name | Finish  | Wall Suitability      | Floor Suitability     | Wet Barefoot | Material / Class       |
|------------|---|-----------------------|-----------------------|--------------|------------------------|
| Kotto      |  Natural | Internal and External | Internal Only         | -            | Glazed Porcelain / Bla |
|            |  Grip    | Internal and External | Internal and External | Yes          | Glazed Porcelain / Bla |

## Floor Values

| Finish  | Colour              | PTV (96)    | PTV (55) | R Value | Wet Ramp | PEI | Traffic          |
|---|---------------------|-------------|----------|---------|----------|-----|------------------|
|  Natural | White Only          | Wet 25 - 35 | -        | -       | -        | IV  | Commercial       |
|   | Biege and Grey Only | Wet 25 - 35 | -        | -       | -        | III | Light Commercial |
|   | Red Only            | Wet 25 - 35 | -        | -       | -        | II  | Domestic         |
|  Grip    | White Only          | Wet 36+     | Wet 36+  | R12     | C        | IV  | Commercial       |
|   | Biege and Grey Only | Wet 36+     | Wet 36+  | R12     | C        | III | Light Commercial |
|   | Red Only            | Wet 36+     | Wet 36+  | R12     | C        | II  | Domestic         |

## Physical Properties - Glazed Porcelain / Bla

| Test and Standard   | Requirement                       | Result | Test and Standard   | Requirement                | Result                          |
|---|-----------------------------------|--------|---|----------------------------|---------------------------------|
|  <b>Length / Width</b><br>EN ISO 10545-2         | $\pm 0.6\% \leq \pm 2\text{mm}$   | Pass   |  <b>Modulus of Rupture</b><br>EN ISO 10545-4     | Min. 35N / mm <sup>2</sup> | Pass                            |
|  <b>Thickness</b><br>EN ISO 10545-2             | $\pm 5\% \leq \pm 0.5\text{mm}$   | Pass   |  <b>Thermal Shock</b><br>EN ISO 10545-9         | Pass                       | Pass                            |
|  <b>Straightness of Side</b><br>EN ISO 10545-2 | $\pm 0.5\% \leq \pm 1.5\text{mm}$ | Pass   |  <b>Frost Resistance</b><br>EN ISO 10545-12    | Resistant                  | Resistant                       |
|  <b>Rectangularity</b><br>EN ISO 10545-2       | $\pm 0.5\% \leq \pm 2\text{mm}$   | Pass   |  <b>Chemical Resistance</b><br>EN ISO 10545-13 | Min. Class B               | Pass                            |
|  <b>Surface Flatness</b><br>EN ISO 10545-2     | $\pm 0.5\% \leq \pm 2\text{mm}$   | Pass   |  <b>Stain Resistance</b><br>EN ISO 10545-14    | Min. Class 3               | Pass                            |
|  <b>Water Absorption</b><br>EN ISO 10545-3     | $\leq 0.5\%$                      | Pass   |  <b>Fire Rating</b>                            |                            | Class A I FL<br>Non Combustible |

## Sustainability Credentials

| Range Name | Material / Class       | EPD | Recycled Content - Tiles | Recycled Content - Packaging |
|------------|------------------------|-----|--------------------------|------------------------------|
| Kotto      | Glazed Porcelain / Bla | -   | Up to 10%                | Up to 100% (Boxes Only)      |

**Note:** Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All floor tiles shown in this literature achieve a PTV (96) Dry 36+ test result. PTV (96): Pendulum Test Value - 4S. PTV (55): Pendulum Test Value - TRL. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. EPD: Environmental Product Declaration. CSV: Colour Shade Variation.

## Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour and patterning are acceptable.

The tiles shown in this literature are quality products and conform to BS EN 14411 as shown in the physical properties listed above.

For a comprehensive colour, size, finish and availability overview along with full technical and sustainability information for all products shown, please visit our website - [www.johnson-tiles.com](http://www.johnson-tiles.com)

- All sizes listed are metric modular.
- For specific suitability details, please contact our technical advice helpline or use the email address provided.
- Johnson Tiles Limited cannot accept responsibility for any tiles that have already been fixed.
- Johnson Tiles Limited reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

All product technical values quoted in this literature are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles Limited are British Standard registered. To find out more, please contact our technical advice helpline on +44 (0)1782 524 111 or email: [technical@johnson-tiles.com](mailto:technical@johnson-tiles.com).

## WHERE TO FIND US

### Head Office

Harewood Street, Tunstall,  
Stoke on Trent, Staffordshire,  
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575  
Email: [info@johnson-tiles.com](mailto:info@johnson-tiles.com)  
[www.johnson-tiles.com](http://www.johnson-tiles.com)

---

### Material Lab Studio

10 Great Titchfield Street,  
London, W1W 8BB,  
United Kingdom

Tel: +44 (0)20 7436 8629  
Email: [info@material-lab.co.uk](mailto:info@material-lab.co.uk)  
[www.material-lab.co.uk](http://www.material-lab.co.uk)

---

### Factory Outlet

Tel: +44 (0)1782 524 040  
Email: [foutlet@johnson-tiles.com](mailto:foutlet@johnson-tiles.com)  
[www.outlet.johnson-tiles.com](http://www.outlet.johnson-tiles.com)

---

### Customer Services

Tel: +44 (0)1782 524 000  
Email: [sales@johnson-tiles.com](mailto:sales@johnson-tiles.com)  
8:30am - 4:30pm (Monday - Friday)

---

### Order A Sample

Tel: +44 (0)1782 524 043  
Email: [samples@johnson-tiles.com](mailto:samples@johnson-tiles.com)

---

### Technical Advice Helpline

Tel: +44 (0)1782 524 111  
Email: [technical@johnson-tiles.com](mailto:technical@johnson-tiles.com)

---

Updated: December 2024



[www.johnson-tiles.com](http://www.johnson-tiles.com) | [f](#) [X](#) [G](#) [d](#) [P](#) [in](#) [v](#)

© 2024 Johnson Tiles Limited