
## **CHROMA**

GLAZED CERAMIC | WALL TILES

PLAIN COLOUR TILES SELECT










### **CHROMA**


Chroma is a stylish collection of slim format ceramic wall tiles, perfect for both commercial and residential design projects. With Gloss and Satin finishes featured across 2 I colours ranging from the neutral, transitional shades of Putty and Sand to the bright, bold tones of Saffron and Sunset, Chroma delivers on character.

Front Cover Image: Saffron Gloss 300x100mm - CHG01A, Sunset Gloss 300x100mm - CHG03A & Dolphin Gloss 300x100mm - CHG09A





#### **Roomset Photography**





VI: Low Shade Variation









#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
I	300x100mm	G Gloss	Arctic, Saffron, Sunset, Poppy, Coal, Tarragon, Ocean, Dolphin, Alloy, Sand, Fawn, Almond & Coffee	8mm	34 Tiles	1.02 m²	I 4.00 kg
		S Satin	Snow, Nightsky, Steel, Pewter, Putty, Seed, Acorn & Mink	8mm	34 Tiles	1.02 m²	14.00 kg

**Note:** All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.





#### Technical Data

#### **Specification**

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Chroma	All Sizes Shown	Internal Only	-	-	VI	Glazed Ceramic [BIII]

#### **Physical Properties**

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO I 0545 - 2	± 0.5% ≤ ± 2mm	≤ ± 0.25%	Modulus of Rupture EN ISO 10545 - 4	Min. I5N / mm²	≥ 25N / mm²
Thickness EN ISO I 0545 - 2	± 10% ≤ ± 0.5mm	± 2.5%	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	± 0.15%	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.4%	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A - B
Surface Flatness EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.3%	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	15% to 17%	Fire Rating	-	Class A I Non Combustible
kg Weight / M²	13.74 kg 8mm thick				

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

#### 

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD	SKA Rating
Chroma	Glazed Ceramic [BIII]	Up to 20%	Up to 100%	Up to 100%	-	-

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Chroma pages on our website.

#### Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- $\bullet$  Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
  Nothing in these statements does or will affect the statutory rights of the consumer.
- ® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.







# For more information about Chroma or any of our other product ranges simply visit www.johnson-tiles.com | f > 0 p in D

#### Where To Find Us

Johnson Tiles Harewood Street, Tunstall, Stoke on Trent,

Staffordshire,

ST6 5JZ

Tel: +44 (0)1782 575 575 Fax: +44 (0)1782 577 377 Email: info@johnson-tiles.com

#### Samples Enquiries

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379

 ${\bf Email: samples@johnson-tiles.com}$ 

#### Technical Helpline

Tel: +44 (0) | 782 524 | | | | | Fax: +44 (0) | | 782 577 379

Email: techadvice@johnson-tiles.com

