

CLASSICS

GLAZED CERAMIC | WALL TILES

STONE MARBLE INTRO SELECT



JOHNSON • TILES 

MADE IN THE UK SINCE 1901

CLASSICS

Influenced by the beauty of natural marbles and stones, Classics provides 5 colour options ranging from timeless White Carrara to warm Crema Marfil. Available in 300x200mm, and certain colours also offering a 600x300mm option, Classics is ideal for residential interiors.

Front Cover Image: Carrara Gloss 600x300mm - CICS1A




Brushed Stone Silk 300x200mm - CICS4A



Roomset Photography



Travertine Satin 600x300mm - CICS2A



Brushed Stone Silk 300x200mm - CICS4A




Carrara Gloss 300x200mm - CICS1A



Colours & Product Codes

V2: Low to Moderate Shade Variation



CARRARA

☐ CICS1A LRV: 83



TRAVERTINE

☐ CICS2A LRV: 63



CREMA MARFIL

☐ CICS3A LRV: 54



BRUSHED STONE

☐ CICS4A LRV: 55




MARBLESTONE

☐ CICS5A LRV: 62



Sizes, Finishes & Availability



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	600x300mm	G Gloss	Carrara	10mm	5 Tiles	0.90 m ²	16.00 kg
		S Satin	Travertine & Crema Marfil	10mm	5 Tiles	0.90 m ²	16.00 kg
2	300x200mm	G Gloss	Carrara & Marblestone	8mm	17 Tiles	1.02 m ²	14.00 kg
		S Satin	Crema Marfil	8mm	17 Tiles	1.02 m ²	14.00 kg
		K Silk	Brushed Stone	8mm	17 Tiles	1.02 m ²	14.00 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.



Carrara Gloss 600x300mm - CICS1A





Technical Data

Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Classics	All Sizes Shown	Internal Only	-	-	V2	Glazed Ceramic [BIII]

Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\leq \pm 0.25\%$	Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm ²	$\geq 25\text{N} / \text{mm}^2$
Thickness EN ISO 10545 - 2	$\pm 10\% \leq \pm 0.5\text{mm}$	$\pm 2.5\%$	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	$\pm 0.15\%$	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.4\%$	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A - B
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	15% to 17%	Fire Rating	-	Class A1 Non Combustible
Weight / M ²	17.78 kg 10mm thick	13.74 kg 8mm thick			

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

Sustainability Information

Range	Material	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Classics	Glazed Ceramic [BIII]	Yes	Up to 20%	Up to 100%	Up to 100%

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.



For more information about Classics or
any of our other product ranges simply visit
www.johnson-tiles.com |      

Where To Find Us

Johnson Tiles

Harewood Street,
Tunstall,
Stoke on Trent,
Staffordshire,
ST6 5JZ

Tel: +44 (0)1782 575 575
Fax: +44 (0)1782 577 377
Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043
Fax: +44 (0)1782 577 379
Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111
Fax: +44 (0)1782 577 379
Email: techadvice@johnson-tiles.com

Launched: July 2017 Updated: January 2022

JOHNSON • TILES 
MADE IN THE UK SINCE 1901